



DRIVEWAY / PAVERS / CONCRETE SLAB CHECKLIST

- BROWARD COUNTY UNIFORM BUILDING APPLICATION**
- CONTRACTOR RECORDS UP-TO-DATE**
- OWNER/BUILDER AFFIDAVIT
(IF OWNER TO ACT AS CONTRACTOR)**
- RECORDED NOTICE OF COMMENCEMENT (IF JOB VALUE OVER \$2,500) FLORIDA BUILDING CODE CHAPTER ONE, BROWARD COUNTY ADMINISTRATIVE PROVISIONS 105.8 – MUST BE RECORDED AND POSTED PRIOR TO THE FIRST INSPECTION**
- 1 SURVEY (INDICATING TOTAL AREA TO PAVE, WIDTH OF DRIVE AND DISTANCE TO PROPERTY LINES/SETBACKS)**
- DRIVEWAY MATERIALS**
 - a. ***PAVER DRIVEWAYS*** – INDICATE PAVERS ON SURVEY PLAN
 - b. ***CONCRETE DRIVEWAY*** – PROVIDE CUT SECTION ON SURVEY PLAN INDICATING CONCRETE THICKNESS WITH TYPE OF REINFORCEMENT TO BE USED AND THICKENED EDGE IF IT IS TO BE INSTALLED
 - c. ***SIDEWALKS*** – REQUIRED TO BE 6 INCHES THICK AT DRIVEWAY AREAS WITH WELDED WIRE MESH
 - d. ***ASPHALT*** – SEE ENGINEERING DEPARTMENT FOR REQUIREMENTS
- FOR CONCRETE SLAB A SOIL TERMITE TREATMENT IF SLAB IS PREPARATION FOR A FUTURE STRUCTURE**